


A6 DKR

Anschluss mit BSP-Überwurfmutter,
passend für Stutzen 60°
mit Rohrgewinde G.

Fitting with BSP union nut,
mating for flare 60°
with pipe thread G.

A6 Standardanschluss

A6 standard connection



DN	Inch	d ₅	d ₇	d ₁₈	l ₄	x	SW ₁	SW ₂	Gewicht Weight	Bestell-Nr. Order No.
		mm	DIN ISO 228		mm	mm	mm	mm	ca. g	
6	1/4"	4,5	G 1/4" (BSP)	M 9 x 1,0	63,0	29	17	19	30	82 06 06
8	5/16"	6,0	G 3/8" (BSP)	M 11 x 1,0	65,0	28	22	19	45	82 06 08
10	3/8"	7,5	G 1/2" (BSP)	M 13 x 1,0	71,0	30	27	22	65	82 06 10
12	1/2"	10,0	G 5/8" (BSP)	M 16 x 1,0	77,5	31	30	27	80	82 06 13
16	5/8"	13,0	G 3/4" (BSP)	M 19 x 1,0	84,5	33	32	32	135	82 06 16
20	3/4"	15,5	G 1" (BSP)	M 23 x 1,0	92,5	37	41	36	230	82 06 20
25	1"	21,0	G 1 1/4" (BSP)	M 29 x 1,5	100,5	40	50	46	365	82 06 25

Armaturenwerkstoff: Stahl, galvanisch
verzinkt und passiviert.
Sonderwerkstoffe und Anschlüsse auf
Anfrage. **Änderungen vorbehalten.**

Fittings made from steel, zinc-plated and
passivated.
For special materials and fittings please
enquire. **Subject to modifications.**